



# ART. 8420.103

Hose reels - s. 430 - 440 - 450

Swivelling hose reel, s.430, for air-water, 20 bar, with black rubber hose 10 m,  $\varnothing$  3/8"



## FLUIDS

FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

## SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

## CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	bar	20
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		swivelling
Material		painted steel
Couplings		zinc plated steel
Hose		996.210
$\varnothing$ and hose length	$\varnothing$ - m	1/2" - 10
Inlet		G 1/2" (f)
Outlet		G 1/2" (m)
Reel flow path		brass - zinc plated steel
Internal drum width	mm	97

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA  
Tel. 0039 0424 571111 - Fax. 0039 0424 571135


info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.



## Overall dimensions

---



RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA  
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.