



ART. 2B3/16117TT52

Diaphragm pumps - in polypropilene and aluminum

Diaphragm pump in aluminum and polypropylene series APPB-12 with multi ported inlet/outlet, membranes and balls in Teflon®, seats in AISI 316 stainless steel and polypropylene and ball valves with spring



FLUIDS	WASTE OIL FRESH OIL ANTIFREEZE WINDSHIELD FLUID WATER DIESEL FUEL ADBLUE® PAINT CLEANING DETERGENT
SECTORS	AERONAUTIC AGRICULTURE AUTOMOTIVE LUBE TRUCK AND INDUSTRIAL VEHICLE CLEANING BUILDING INDUSTRY AND ROAD CONSTRUCTION RAILWAY TRANSPORT CHEMICAL INDUSTRY MANUFACTURING INDUSTRY MINING SHIPPING AND OFFSHORE
CERTIFICATIONS	ATEX (ZONE 2) ATEX (ZONE 22)

Features	UM	Value
Flow rate	l/min	50
Ratio		1:1
Compatible fluids		antifreeze and windshield washing liquid
Motor and inside flanges material		aluminum
Wetted parts		polypropylene
Ball valve material		Teflon®
Air inlet connection		G 3/8" (f)
Fluid inlet-outlet connection		G 3/4" (f) x G 1/2" (f)
Air working pressure	bar	2 ÷ 6
Max supply pressure	bar	8
Average air consumption	l/min	400
Noise level	dB	75
Fluid temperature	°C	-10 ÷ +65
Max solids diameter	mm	ø 1,5
Suction-delivery ball valve with spring		cylindrical ball valve with spring
Packing	N° - m³	1 - 0,015
Weight	kg	7,5
Dimensions (A-B-C)	cm	17,8 - 21,8 - 32,6

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.