



ART. 44060

Waste oil gravity and suction drainers

Combination air operated oil suction drainer 65 litre without transparent chamber



FLUIDS

WASTE OIL

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION

CERTIFICATIONS

PRESSURE EQUIPMENT DIRECTIVE

Features	UM	Value
Tank capacity	litres	65
Max draining capacity	litres	52
Prechamber capacity	litres	-
Bowl capacity	litres	15
Air pressure for depressurisation	bar	6,5 ÷ 7
Depressurisation time	min	2
Noise level	dB	75
Suction speed	l/min	1,5 ÷ 2
Total suction capacity	litres	43 ÷ 45
Discharging/Suction hose	m	2/2
Max pressure for discharging	bar	0,5
Set of probes	P/N	45560
Packing	N° - m ³	3 - 0,330
Weight	kg	34,6
Dimensions (A-B-C)	cm	62 - 42 - 134
Dimensions (D)	cm	175

RAASM SpA

via Marangoni 33, 36022 - S. Zeno di Cassola (VI) - ITALIA
Tel. 0039 0424 571111 - Fax. 0039 0424 571135

info@raasm.com - www.raasm.com

Copyright © 2020 All rights reserved to RAASM S.p.A.